

SUPER STRAP POLYMER BANDING



NON CONDUCTIVE BANDING IS DESIGNED TO BE LINEMAN SAFE, AND WITH ADVANCED TEXTILE SCIENCE IT IS DURABLE AND STRONG.



100% POLYMER NON-CONDUCTIVE BANDING


INTEGRATED NYLON FILAMENTS ENHANCE HIGH HOLDING STRENGTH ABILITIES

3/4" STRAP HOLDS $\geq 2,900$ LBF* PER BAND

UV-RESISTANT POLYMER IS LIGHTWEIGHT AND DURABLE

POLYMER ELIMINATES RISK OF DISSIMILAR METAL CAUSE CORROSION FAILURES

QUICK-ATTACH, TAMPER-PROOF BUCKLES



NYLON FILAMENT
INTEGRATION

*MEASURED ON 600MM DIAMETER



SYSTEM RELIABILITY SOLUTIONS
POWERLINESENTRY.COM // SALES@POWERLINESENTRY.COM // 970.599.1050



SUPER STRAP POLYMER BANDING



SUPER STRAP
BANDING
ASSEMBLED



SUPER STRAP
BANDING ROLL
SSB-BA-3/4-98



SUPER STRAP
BUCKLE
SSB-BU-3/4



SUPER STRAP
TOOL
SSB-AT-3/4

SKU	LENGTH
SSB-BA-3/4-98	98' L x 3/4" W
SSB-BA-3/4-196	196' x 3/4" W
SSB-BA-3/8-410	410' x 3/8" W
SSB-BU-3/4	3/4" BUCKLE FOR SSB-BA-3/4-98 AND SSB-BA-3/4-196
SSB-BU-3/8	3/8" BUCKLE FOR SSB-BA-3/8-410
SSB-AT-3/4	TIGHTENING TOOL FOR SSB-BA-3/4-98 AND SSB-BA-3/4-196
SSB-AT-3/8	TIGHTENING TOOL FOR SSB-BA-3/8-410

TESTS	RESULTS
UL-94 FLAMMABILITY	HB
IEEE 1656 / 5.6 ULTRAVIOLET AGING / ASTM G-155	PASSED
ISO 4892-2 / WEATHERED TENSILE STRENGTH	PASSED

