



# Flexible sleeve insulator covers




Flexible insulator covers protect energized insulator neck equipment as well as the conductor, the flexible sleeves can accommodate any system configuration.



V-O  
flame retardant



Very hotstick  
friendly



Rated at <69 kV  
insulation

## Only flexible sleeve cover in the industry

- Available in standard pin, clamp top, or vise top cap fitments
- Arrives in 1 piece—no chance for sleeve separation, no on-site assembly
- Flexible silicone rip-stop™ line hose sleeves accommodate all structure configurations/angles
- Minimum 70 in (178 cm) of coverage provides superior protection
- Covers energized portion of the insulator, allowing sheds to naturally clean and be easily viewed during inspections
- Double top versions are adjustable in width for a perfect fit
- UL 94 V-0 flame retardant material
- Hotstick friendly, snaps into position - no locking pins



videos + more

SKU	Type	Length	I.D.	Insulator	kV rating	Min qty
CC-DFLEXCF-100	CF	91-95 0"/2.03 m	1"/2.54 cm	Double ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	5
CC-DFLEX-CF-125	CF	91-95"/2.03 m	1 1/4"/3.17 cm	Double ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	4
CC-DFLEX-JK-100	JK	91-95"/2.03 m	1"/2.54 cm	Double ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	5
CC-DFLEX-JK-125	JK	91-95"/2.03 m	1 1/4"/3.17 cm	Double ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	4
CC-DFLEX-TR-100	Trunnion	91-95"/2.03 m	1"/2.54 cm	Trunnion	< 44	5
CC-DSTFLEX-CF-100	CF	91-95"/2.03 m	1"/2.54 cm	Double side tie ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	5
CC-DSTFLEX-CF-125	CF	91-95"/2.03 m	1 1/4"/3.17 cm	Double side tie ansi 55-3, 55-4, 55-5 55-6, 55-7,	< 35	4
CC-STFLEX-CF-100	CF	70"/1.8 m+	1"/2.54 cm	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	10
CC-STFLEX-CF-125	CF	70"/1.8 m+	1 1/4"/3.17 cm	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	8
CC-FLEX-CF-100	CF	70"/1.8 m+	1"/2.54 cm	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	10
CC-FLEX-CF-125	CF	70"/1.8 m+	1 1/4"/3.17 cm	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	8
CC-FLEX-JK-100	JK	70"/1.8 m+	1"/2.54 cm	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	10
CC-FLEX-JK-125	JK	70"/1.8 m+	1 1/4"/3.17 cm	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	8
CC-FLEX-TR-100	Trunnion	70"/1.8 m+	1"/2.54 cm	Trunnion	< 44	10
CC-FLEX-TR-125	Trunnion	70"/1.8 m+	1 1/4"/3.17 cm	Trunnion	< 44	10
CC-FLEX-TR-125-69	Trunnion	70"/1.8 m+	1 1/4"/3.17 cm	Trunnion	< 69	10
CC-FLEX-UCT-125	Clamp top	70"/1.8 m+	1 1/4"/3.17 cm	Bolt actuated top clamp	< 46	10
CC-FLEX-UVT-125	Vise top	70"/1.8 m+	1 1/4"/3.17 cm	Vise top	< 35	10
CC-CF *	CF	21" / 53 cm	-	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	25
CC-JK *	JK	21" / 53 cm	-	Ansi 55-3, 55-4, 55-5, 55-6, 55-7	< 35	25
CC-TR *	Trunnion	21" / 53 cm	-	Trunnion	< 69	10

Tool	
CC-FLEX-AT-K	Hotstick compatible installation tool set for all flexible conductor covers

Tests	Results
IEEE 1656 / 5.2 dry withstand	>20 kV
IEEE 1656 / 5.6 ultraviolet aging / ASTM G-155	1,000 hrs
ASTM D149 dielectric strength	938 V/MIL (36.9 kV/mm)
ASTM D 3638 comparative tracking index	526 V
ASTM D-638 / D-1822 original tensile impact	56.7 FT LB/SQ IN
ASTM D-638/ D-1822 weathered tensile strength	51.04 FT LB/SQ IN

\* Cap with two retention sleeves for installation over line hose

